

Magno Volume Product Information



Magno Volume is a coated fine paper available in sheets and reels for offset printing

Technical specifications

Parameter	Standard	Unit														
Basis weight	ISO 536	g/m ²	80	90	100	115	130	135	150	170	200	250	300	350	400	450
CIE whiteness (D65/10°)	ISO 11475	%	124	124	125	126	126	126	126	126	126	127	127	128	128	128
Opacity	ISO 2471	%	92	94	95	96	97	97	98	98	98,5	99	99	100	100	100
Gloss TAPPI 75°	ISO 8254-1	%	14	14	14	14	14	14	14	14	14	20	20	22	22	22
Bulk	ISO 534	cm ³ /g	1,08	1,08	1,08	1,08	1,08	1,08	1,08	1,08	1,08	1,03	1,03	1,05	1,05	1,06

Mill Certification

EMAS	The environmental performance is monitored and continuously improved according to the requirements of Eco-Management and Audit Scheme (EMAS).
ISO 9001	The quality of the manufacturing is managed according to the requirements of ISO 9001.
ISO 14001	The environmental aspects of the mill are managed according to the requirements of ISO 14001.
ISO 50001	The energy consumed and the emissions generated by the mill are managed according to ISO 50001.
FSC® FSC-C015022	All fibers from sustainability and controlled sources. FSC® may have limited availability, please check with your local sales office.
PEFC™ PEFC/07-32-76	All fibers from sustainability and controlled sources. PEFC™ may have limited availability, please check with your local sales office.
OHSAS 18001	The health and safety of the mill employees are managed according to the requirements of OHSAS 18001.

Product Certification

PEFC™ PEFC/07-32-76	All fibers from sustainable and controlled sources. PEFC™ may have limited availability, please check with your local sales office.
FSC® FSC-C015022	All fibers from sustainability and controlled sources. FSC® may have limited availability, please check with your local sales office.
	Only approved chemicals used, in compliance with BfR recommendation XXXVI 'Paper and Board for Food Contact'. Magno Volume is suitable for direct contact with dry and fatty foodstuff.
	Meets the purity requirements (heavy metal content) of EN 71-3 'Toy Safety', part 3 'Migration of certain elements' and part 9 'Organic chemical compounds'.
	The key environmental parameters of the product are presented at the Paper Profile.
	Archivability tested according to the requirements of DIN 6738, Lifespan class - LDK 24-85.
ECF	Pulp is bleached without the use of elemental chlorine (ECF).
Dry toner suitable	Dry toner: Suitable for dry toner.

Packaging of product complies with packaging and waste directive 94/62/EC (article 11).
Magno Volume is fully recyclable.